

Serial No.: 10/751,544

CLAIMS:

1-7. (Canceled)

8. (Currently Amended) ~~The guide catheter apparatus of claim 7,~~ A guide catheter apparatus, comprising:

(a) a guide catheter portion comprising a plurality of electroactive polymer actuators disposed along its axial length, said actuators changing guide catheter portion shape based upon received control signals; and

(b) a control unit coupled to said plurality of actuators and sending said control signals to said plurality of actuators, wherein each of said plurality of electroactive polymer actuators comprises (a) an active member portion, (b) a counter-electrode portion and (c) a region comprising an electrolyte disposed between said active member portion and said counter-electrode portion, wherein said active member portion, said counter-electrode portion and said region comprising an electrolyte are disposed between a substrate layer and a barrier layer, wherein said substrate layer is in the shape of a tube.

9. (Currently Amended) ~~The guide catheter apparatus of claim 8,~~ A guide catheter apparatus, comprising:

(a) a guide catheter portion comprising a plurality of electroactive polymer actuators disposed along its axial length, said actuators changing guide catheter portion shape based upon received control signals; and

(b) a control unit coupled to said plurality of actuators and sending said control signals to said plurality of actuators, wherein each of said plurality of electroactive polymer actuators comprises (a) an active member portion, (b) a counter-electrode portion and (c) a region comprising an electrolyte disposed between said active member portion and said counter-electrode portion, wherein said active member portion, said counter-electrode portion and said region comprising an electrolyte are disposed between a substrate layer and a barrier layer, wherein said substrate layer is in the shape of a tube.

Serial No.: 10/751,544

wherein at least a portion of said electroactive polymer actuators are adapted to contract in a direction parallel to an axis of said tube.

10-39. (Cancelled)

40. (New) A guide catheter apparatus, comprising:

(a) a guide catheter portion comprising a plurality of electroactive polymer actuators disposed along its axial length, said actuators changing guide catheter portion shape based upon received control signals; and

(b) a control unit coupled to said plurality of actuators and sending said control signals to said plurality of actuators, wherein each of said plurality of electroactive polymer actuators comprises (a) an active member portion, (b) a counter-electrode portion and (c) a region comprising an electrolyte disposed between said active member portion and said counter-electrode portion, and wherein said active member portion, said counter-electrode portion and said region comprising an electrolyte are disposed between a substrate layer and a barrier layer.

41. (New) The guide catheter apparatus of claim 8, wherein said electroactive polymer actuators comprise an electroactive polymer selected from the group consisting of polyaniline, polypyrrole, polysulfone, and polyacetylene.

42. (New) The guide catheter apparatus of claim 41, wherein said electroactive polymer actuators comprise polypyrrole.

43. (New) The guide catheter apparatus of claim 8, wherein at least a portion of said actuators are in tension with one another.

Serial No.: 10/751,544

44. (New) The guide catheter apparatus of claim 8, wherein said plurality of electroactive polymer actuators are disposed along at least 5% of the fully inserted axial length of the guide catheter portion.

45. (New) The guide catheter apparatus of claim 8, wherein said guide catheter portion further comprises a plurality of strain gauges.

46. (New) The guide catheter apparatus of claim 8, wherein said guide catheter portion further comprises a structural element selected from the group consisting of (a) a tubular network comprising at least one metallic filament, (b) a tubular interconnected network of articulable segments, (c) a helical structure comprising at least one metallic filament, and (d) a patterned tubular sheet.

47. (New) The guide catheter apparatus of claim 8, wherein said control signals are sent from said control unit to said actuators over a multiplexed cable.

48. (New) The guide catheter apparatus of claim 8, wherein said control unit comprises a personal computer.

49. (New) The guide catheter apparatus of claim 8, wherein said electroactive polymer actuators are controllable to provide a desired curvature to said guide catheter portion at each of a plurality of loci along the length of said catheter portion.

50. (New) The guide catheter apparatus of claim 8, wherein said control signals correspond to a user selectable shape for said guide catheter portion.

51. (New) The guide catheter apparatus of claim 8, wherein said control unit comprises an electronic memory, and wherein said user selectable shape for said guide catheter portion is stored in said electronic memory.

Serial No.: 10/751,544

52. (New) The guide catheter apparatus of claim 8, said control signals are generated using a manual steering device.

53. (New) The guide catheter apparatus of claim 8, wherein said control signals are generated by a shape-generating algorithm within said control unit using medical diagnostic imaging data.

54. (New) The guide catheter apparatus of claim 53, wherein said medical diagnostic imaging data is angiogram data.

55. (New) The guide catheter apparatus of claim 8, wherein said catheter portion comprises a lead module and a plurality of following modules, and wherein said guide catheter portion is adapted to travel in such a way that, when each following module reaches a position previously occupied by said lead module, said actuators cause said each following module to replicate the orientation of said lead module at said position.

56. (New) The guide catheter apparatus of claim 55, wherein position data is provided by a depth gauge or a linear displacement module.

57. (New) The guide catheter apparatus of claim 55, wherein lead module orientation data is provided by strain gauges within said lead module.

58. (New) The guide catheter apparatus of claim 8, wherein said control signals are sent from said control unit to said actuators over a wireless interface.

59. (New) The guide catheter apparatus of claim 8, wherein said plurality of electroactive polymer actuators are disposed along at least 10% of the fully inserted axial length of the guide catheter portion.

Serial No.: 10/751,544

60. (New) The guide catheter apparatus of claim 8, wherein said plurality of electroactive polymer actuators are disposed along at least 25% of the fully inserted axial length of the guide catheter portion.

61. (New) The guide catheter apparatus of claim 8, wherein said plurality of electroactive polymer actuators are disposed along at least four centimeters of the guide catheter.

62. (New) The guide catheter apparatus of claim 8 wherein said plurality of electroactive polymer actuators are disposed along at least ten centimeters of the guide catheter.